



1D & 2D



Duo
Near &
Far



CMOS



USB



RS232



Laser
aimer



IP54



1.8M
drop



EasySet



Warranty
5 Years



**HR52 Bonito
Duo**
Handheld Scanners

Features

Duo Near & Far Scanning

By incorporating Newland's self-developed barcode decoding technology and advanced optical technology, the HR52 Bonito Duo combines excellent near-distance scanning with superior far-range scanning, bridging the gap between affordable retail and advanced warehouse and logistics solutions.

Ultra-Rugged Design

The HR52 Bonito Duo, built into an IP54-sealed and 1.8m drop-resistant housing, can stand up to tough environments. With a trigger lifespan of 10 million times, this handheld scanner provides a guarantee of exceptional reliability and durability in any application.

Precise Laser Aiming

The HR52 Bonito Duo is equipped with an optimized clear laser aiming spot that remains highly visible in both close proximity and at a distance, regardless of the indoor or outdoor environment. This advanced feature guarantees convenient and precise targeting of barcodes.

Powerful Data Editing Capability

The HR52 Bonito Duo offers effortless customization of scanned data via the user manual, catering to diverse application requirements. Additionally, it provides supporting software (EasySet) to address various data editing needs, ensuring seamless integration into different workflows.



Suggested industries



Retail



Warehousing



Logistics



Manufacturing



Healthcare

HR52 Bonito Duo Technical specifications

Data Capture

1D	All major 1D symbologies, including EAN-13, EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code 128, Code93, ITFF6-14, Interleaved 2 of 5, Industrial 25, Standard 25, Matrix 25, GS1 Databar, Code 39, Code 11, MSI-Plessey, Plessey.
2D	All major 2D symbologies, including PDF417, QR Code, Data Matrix, Aztec, Maxicode.
Image Sensor	1280x800 CMOS
Aiming	650nm laser diode
Illumination	White LED
Depth of Field EAN 13 (13mil)	20cm-180cm
Depth of Field Code 39 (10mil)	20cm-140cm
Depth of Field Code 39 (100mil)	50cm-600cm
Depth of Field Code128 (100mil)	44cm-980cm
Depth of Field QR (55mil)	25cm-300cm
Field of View	Near Camera: Horizontal 42°; Vertical 28°; Far Camera: Horizontal 16°; Vertical 13°
Scan Angle	Roll: 360°, Pitch: ±55°, Skew: ±50°
Minimal Print Contrast	20%

Physical

Current @ 5VDC Operating	Typical (Near Camera: 414mA, Far Camera: 728mA); Maximum (Near Camera: 631mA, Far Camera: 1065mA)
Current @ 5VDC Standby	71mA
Dimensions (mm)	172.5×77.5×95.5mm
Input Voltage	5V DC±5% @1A
Interfaces	RS232/USB
Notifications	Beep, LED indicator, vibration
Power Consumption	Near Camera: 2071mW, Far Camera: 3642mW
Weight	271g

Environmental

Operating Temperature	-20°C to 50°C (-4°F to 122°F)
Storage Temperature	-30°C to 70°C (-40°F to 158°F)
Humidity	5% to 95% (non-condensing)
Electro Static Discharge (ESD)	±8 kV (air discharge), ±12kV (direct discharge)
Drop	1.8m drop to concrete
IP Rating	IP54

Software

Configuration Tools	EasySet
---------------------	---------

Warranty

Standard	5 years
----------	---------

Newland EMEA HQ

+31 (0) 345 87 00 33

info@newland-id.com

newland-id.com

Feel free to contact us or a partner near you

visit newland-id.com/partners

Specifications are subject to change without notice

© Newland EMEA 2023, all rights reserved