

IQ Color 2000D Opaque


FEATURES

- Direct thermal, opaque paper label with a permanent acrylic adhesive
- Ability to print vibrant color on demand in predefined zones to be used as a visual cue
- Offers flexibility over traditional preprinted labels, requiring fewer roll changes for customers using multiple SKUs
- Limited resistance to moisture and abrasion
- Choose from 8 standard direct thermal colors Magenta, Red, Orange, Yellow, Green, Cyan, Blue, and Purple (10017732RM)

MATERIAL CONSTRUCTION

Component	Description	Caliper
Facestock	White coated opaque direct thermal paper	2.8 mil
Adhesive	High performance, acrylic-based	0.8 mil
Liner	40 lb. semi-bleached, kraft stock	2.5 mil
	TOTAL ± 10%	6.1 mil

ADHESIVE STRENGTH



*Attraction between adhesive and surface is so great that the facestock rips.

TEMPERATURE PERFORMANCE

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
40° F (4° C)	-65° F to 120° F (-54° C to 49° C)	72° F (22° C) at 50% RH

EXPECTED EXTERIOR LIFE

Not recommended for outdoor use

CHEMICAL RESISTANCE

	Chemical	Direct Thermal			
Weak	Blood	NR			
	Body Fluid	NR			
	Salt Water	NR			
	Water	NR			
	Window Cleaner	NR			
Moderate	Alcohol	NR			
	Ammonia	NR			
	Bleach	NR			
	IPA	NR			
Harsh	Gasoline	NR			
	Grease	NR			
	Oil	NR			
Extreme	Acetone	NR			
	IR Reflow	NR			
	MEK	NR			
	TCE	NR			
	Xylene	NR			

SUGGESTED APPLICATIONS

Retail — Price
Markdowns requiring
a "cover-up" label



 Customers currently using an ink jet or laser color solution for labeling



Recommended – Test in Your Application NR Not Recommended

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.



IQ Color 2000D Opaque

LIFESPAN OF IQ COLOR INKS

IQ Color Ink	Lifespan (months) for typical office and warehouse conditions (direct lighting)	Lifespan (months) for typical office <u>filing</u> conditions (no light exposure)
Yellow	1	12
Green	1	12
Red	3	12
Orange	3	12
Cyan	6	12
Magenta	6	12
Blue	6	12
Purple	6	12
Black	6	12

RECOMMENDED PRINT SPEEDS

Normal (picket-fence) codes -- 6 ips maximum Rotated (ladder) codes -- 3 ips maximum

BAR CODE DENSITY

Minimum 10 mil narrow bar normal codes (2 dot code at 203 dpi) Minimum 15 mil narrow bar rotated codes (3 dot code at 203 dpi)

PRINTHEAD CLEANING

Zebra recommends cleaning with an alcohol swab after each roll of media is printed.

All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com

©2018 ZIH Corp and/or its affiliates. All rights reserved. ZEBRA and the stylized Zebra head are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners.