

HONEYWELL GRANIT™ ULTRA ACCESSORIES GUIDE

Accessories Guide

Honeywell

TABLE OF CONTENTS

- 3 Stands, Holders, Holsters, Misc
- 4 Access Points, Batteries, Charge and Communication Bases, and Chargers
- 5 Heaters
- 6 Cables
- 7 Power Supplies for Charge/Comm Bases
- 7 Power Supplies for Cabled Connections

STANDS, HOLDERS, HOLSTERS, MISC



HOLDER-010-U

Wall-Mount Cup

Holder Kit: Plastic bracket facilitates mounting of scanner to wall; two mounting screws included in kit.



HOLSTER-INDUSTRIAL

Granit Holster

Securely holds Granit Ultra and Granit XP scanners, leaving hands free to accomplish tasks.



STND-33F00-012-4

Flexible Presentation Stand


Stand: gray, 9" flexible rod, weighted base, Granit cradle.



TOOLBAL

Take-Up Reel/Tool Balancer

Suspension reel commonly used for scanner mounting/retention on vehicles and in fixed locations.



VMHOLDER2K

Vehicle mount holder

Vehicle Mount Cup: Contains vehicle mount Granit scanner cup with 1 in. dia. ball joint attachment. Recommended use with VMHOLDER3K or VMHOLDER4K, not included.



VMHOLDER3K

Vehicle mount holder

Vehicle mount kit: Contains adjustable arm with 1 in. dia. ball joints and circular mounting plate. Recommended use with VMHOLDER 2K cup (not included).



VMHOLDER4K

Vehicle mount holder

Vehicle mount kit: Contains adjustable arm with 1 in. dia. ball joints and square post clamp base for posts up to 3 in. wide and 2.5 in thick. Recommended use with VMHOLDER 2K cup (not included).



2105IENDCAP

Battery end cap

Cordless Granit Ultra end cap (battery door) for 2105i models



199XILNYRDPLT

Lanyard plate

Replacement metal lanyard plate for connection to tool balancer. Compatible with Granit Ultra and Granit XP models. Pack of 1.



199XIORING

Corded IP65/67 O-Ring

O-ring for IP sealing with Granit Ultra and Granit XP scanner cables. Pack of 10.



CCB23ORING

Cordless IP65 O-Ring

O-ring for IP65 sealing with Granit Ultra base cables. Pack of 10.



PSORING

Cordless IP65 O-Ring

O-ring for IP65 sealing with Granit Ultra power adapter (5V3A) cables. Pack of 10.

ACCESS POINTS, BATTERIES, CHARGE AND COMMUNICATION BASES, AND CHARGERS



AP-100BT-07N

Bluetooth Access Point

Access point for Granit Ultra and XP scanners. Class 1 Bluetooth, 100m, up to 7 Granit Ultra scanners can be connected (cables sold separately).



AP-05-100BT-07N

Bluetooth Access Point

Access point for Granit Ultra, XP, and 1981i scanners. Class 1 Bluetooth, 100m, up to 7 Granit scanners can be connected (cables sold separately).



BAT-SCN11

Smart Battery Pack

Battery: Lithium-ion battery for Granit Ultra and Xenon Ultra cordless scanners.



CCB23-100BT-07N

Granit Ultra Charge/Communication Base

Granit Ultra Base: Charge and communication. Class 1 Bluetooth. 100m (300'), up to 7 scanners can be connected. Compatible with RS232/USB/KBW cables (sold separately).

1. Indicates characters designating regional configuration

HEATERS



520-24-H3

Scanner Heater with Cable Retractor

24V heater for Granit scanners in freezer environments.



520-36/48-H3

Scanner Heater with Cable Retractor

36-48V heater for Granit scanners in freezer environments.



CABLES

CBL-020-300-C00

RS-232 Cable

Cable: RS232 (5V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9, w/o ferrite.

CBL-020-300-C00-01

RS-232 Cable

Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3m (9.8 ft), coiled, 5V external power with option for host power on pin 9, w/o ferrite.

CBL-020-300-C00-02

RS-232 Cable

Cable, Industrial (for freezer temps): RS-232 (5V signals), black, DB9 Female, 3 m (9.8 ft), coiled, 5V external power with option for host power on pin 9, with ferrite.

CBL-020-500-C00

RS-232 Cable

Cable: RS232 (+5V signals); black, DB9 female, 5m (16 ft), coiled, external power with option for host power on pin 9, w/o ferrite.

CBL-020-350-S00

RS-232 Cable

Cable: RS-232 (5V signals), black, DB9 female, 3m (9.8'), straight, external power with option for host power on pin 9, w/o ferrite.

CBL-120-300-C00

RS-232 Cable

Cable: RS-232 (+/-12V signals), black, DB9 Female, 3m (9.8'), coiled, 5V external power with option for host power on pin 9, w/o ferrite.

CBL-220-300-C00

RS-232 Cable

Cable: RS-232 (5V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9, Wincor Beetle.

CBL-320-300-C00

RS-232 Cable

Cable: RS-232 (+/- 12V signals), black, DB9 Male, 3m (9.8'), coiled, external power with option for host power on pin 9, w/o ferrite.

CBL-500-300-C00

USB Cable

Cable: USB, black, Type A, 3m (9.8'), coiled, 5V host power, w/o ferrite.

CBL-500-300-C00-07

USB Cable

Cable: Industrial (for freezer environments)USB, black, Type A, 3m (9.8'), straight, 5V host power.

CBL-500-300-S00

USB Cable

Cable: USB, black, Type A, 3m (9.8'), straight, 5V host power, w/o ferrite.

CBL-500-300-S00-01

USB Cable

Cable, Industrial (for freezer environments) USB, black, Type A, 3m (9.8'), straight, 5V host power, w/o ferrite.

CBL-500-500-C00

USB Cable

Cable: USB, black, Type A, 5m (16.4'), coiled, 5V host power, w/o ferrite.

CBL-501-300-S00

USB Cable

Cable: USB Granit scanner cable, compatible with USB D9 connectors on VM series docks, w/o ferrite.

CBL-503-300-C00

USB Cable

Cable: USB, black, 12V locking, 3m (9.8'), coiled, 5V host power, w/o ferrite.

CBL-503-300-S00

USB Cable

Cable: USB, black, 12V locking, 3m (9.8'), straight, 5V host power, w/o ferrite.

CBL-503-500-C00

USB Cable

Cable, USB, black, 12V locking, 5m (16.4'), coiled, 5V host power, w/o ferrite.

CBL-720-300-C00

KBW Cable

Cable: KBW, black, PS2, 3m (9.8'), coiled, 5V external power with options for host power, w/o ferrite.

CBL-720-370-C00

PS-2 Cable

Cable: USB, black, PS-2 Keyboard Wedge, 3.7 meter (11.3 ft) Coiled, 5V, w/o ferrite.

CBL-800-300-C00

USB C Cable


Cable: USB C, 3m (9.8'), coiled, 5V host power, w/o ferrite.

CBL-801-370-C00

RS-232 Talkman Cable

Cable, RS-232 (5V signals), black, Granit to Vocollect Talkman, 3.7m (12 ft), coiled, host 5V power only, w/o ferrite.


POWER SUPPLIES FOR CHARGE/COMM BASES



PS-05-3000-W-U

Granit Ultra CCB Power Supply

Granit Ultra Power Supply for charge and communication base (CCB23), 5VDC 3.0A, 100-240VAC @50-60HZ. . Includes plug adapters for type A, C, G, and I.



POWER SUPPLIES FOR CABLED CONNECTIONS

46-00525-6

Power Supply – NA Plug

Power Supply: Type A plug (NA), 1.0A @ 5.2VDC, 90-255VAC @ 50-60Hz, LV6, for use with cabled connections and Xenon and Voyager bases.

46-00528


Power Supply – ANZ Plug

Power Supply: Type I plug (ANZ, Argentina, China), 1.0A @ 5.2VDC, 90-255VAC @ 50-60Hz, LV6, for use with cabled connections and Xenon and Voyager bases.

46-00526-6

Power Supply – EU Plug

Power Supply: Type C plug (EU), 1.0A @ 5.2VDC, 90-255VAC @ 50-60Hz, LV6, for use with cabled connections and Xenon and Voyager bases.



For more information

automation.honeywell.com

Honeywell Industrial Automation

855 South Mint Street
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Granit Ultra Accessories Guide A4 | Rev A | 01/25
©2025 Honeywell International Inc.

Honeywell