

## Z-Perform 1000D Removable

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	✓
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)	✓		Deep Freeze	
	Thermal Transfer (Ribbon Required)			High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
			Chemical Resistance	-	

Note: Z-Perform 1000D Removable is not recommended for applications involving long term exposure to sunlight, extreme heat or on a PVC surface.

### Additional Features

- **BPA Free facestock**
- No ribbon required for direct thermal printing, therefore only one stock item needed
- Produces high contrast black images with recommended Zebra printers
- Good adhesion and clean removability on a wide variety of surfaces
- ISEGA approval for direct contact with dry and non-fatty foodstuffs
- Adhesive complies with European food regulations EC 1935/2004, EU 10/2011 and FDA 175.105 for direct contact with dry and non-fatty foodstuffs

### Suggested Applications

- Indoor general purpose labelling and food labelling
- Labelling of most packaging materials
- Removable shelf-edge labelling, product and price labelling in retail
- Product Identification
- Work in progress labelling
- Removable labels for boxes, pallets, shelves or tote bins

## Technical Specifications

	Description	Caliper
Facestock	Matte white uncoated thermal imaging paper	79 microns
Adhesive	Removable rubber adhesive	12 microns
Liner	60gsm glassine liner	51 microns
Total		142 microns ±10%

**Recommended Zebra Printers:**

Mobile, desktop, mid-range and high-performance thermal printers

**Minimum Application Temperature:**

-10°C

When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:**

-30°C to 70°C

Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:**

6 months duration when stored at 20°C at 50% RH

Storage of product before use

**Expected Life Span in Application:**

Indoor use, for up to 1 year

Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material please order sample roll SAMPLE30821.